

## NAMD 3.0.1 - MPI

### Webpage

<http://www.ks.uiuc.edu/Research/namd/>

### Version

3.0.1

### Build Procedure

- GCC 13.1.1 (gcc-toolset-13)
- Intel MKL 2024.1
- Open MPI 4.1.6

### Files Required

- NAMD\_3.0.1\_Source.tar.gz
  - tcl and tcl-threaded were obtained from <http://www.ks.uiuc.edu/Research/namd/libraries>
  - fftw of MKL was used

### Build Procedure

```
#!/bin/sh

VERSION=3.0.1
CHARM_VERSION=8.0.0
WORKDIR=/gwork/users/${USER}
SOURCEDIR=/home/users/${USER}/Software/NAMD/${VERSION}
NAME=NAMD_${VERSION}_Source
TARBALL=${SOURCEDIR}/${NAME}.tar.gz

LIBURL=http://www.ks.uiuc.edu/Research/namd/libraries
TCL=tcl8.5.9-linux-x86_64
TCL_URL=${LIBURL}/${TCL}.tar.gz
TCL_THREADED=tcl8.5.9-linux-x86_64-threaded
TCL_THREADED_URL=${LIBURL}/${TCL_THREADED}.tar.gz

TARBALL_TCL=${SOURCEDIR}/${TCL}.tar.gz
TARBALL_TCL_THREADED=${SOURCEDIR}/${TCL_THREADED}.tar.gz

PARALLEL=12

#-----
umask 0022

export LANG=""
export LC_ALL=C

module -s purge
module -s load gcc-toolset/13
module -s load mkl/2024.1
module -s load openmpi/4.1.6/gcc13

cd ${WORKDIR}
if [ -d ${NAME} ]; then
  mv ${NAME} namd_erase
  rm -rf namd_erase &
fi

tar zxf ${TARBALL}
cd ${NAME}
tar xf charm-${CHARM_VERSION}.tar
```

```
cd charm-${CHARM_VERSION}

export CC=gcc
export CXX=g++
export F90=gfortran
export F77=gfortran
export MPICXX=mpicxx
export MPICC=mpicc
export MPIF90=mpif90
export MPIF77=mpif90

./build charm++ mpi-linux-x86_64 \
  --no-build-shared --with-production -j${PARALLEL}
cd ../

tar zxf ${TARBALL_TCL}
mv ${TCL} tcl
tar zxf ${TARBALL_TCL_THREADED}
mv ${TCL_THREADED} tcl-threaded

./config Linux-x86_64-g++ \
  --charm-arch mpi-linux-x86_64 \
  --with-mkl \
  --with-python

cd Linux-x86_64-g++

make -j${PARALLEL}
make release
```

## Notes

- same procedure as 3.0