

## Gromacs 5.0.6 for Primargy

### ウェブページ

<http://www.gromacs.org/>

### バージョン

5.0.6

### ビルド環境

- Intel Compiler 15.0.2
- Cuda compilation tools, release 7.0, V7.0.27
- Intel MPI 5.0.3.048
- cmake 2.8.8

### ビルドに必要なファイル

- [gromacs-5.0.6.tar.gz](#)
- [no-gcc-version.patch](#)
- [int128.patch](#)

### パッチファイル

#### no-gcc-version.patch

```
--- cmake/gmxManageNvccConfig.cmake.orig 2014-07-09 09:43:31.108489646 +0900
+++ cmake/gmxManageNvccConfig.cmake 2014-07-09 09:44:24.668688300 +0900
@@ -109,16 +109,16 @@
     # as even with icc used as host compiler, when icc's gcc compatibility
     # mode is higher than the max gcc version officially supported by CUDA,
     # nvcc will freak out.
-   if (UNIX AND CMAKE_C_COMPILER_ID MATCHES "Intel" AND
-       CUDA_HOST_COMPILER_AUTOSET)
-       if (CUDA_VERSION VERSION_LESS "4.1")
-           message(STATUS "Setting Intel Compiler compatibity mode to gcc 4.4 for nvcc host compilation")
-           set(CUDA_HOST_COMPILER_OPTIONS "${CUDA_HOST_COMPILER_OPTIONS};-Xcompiler;-gcc-version=440;")
-       else()
-           message(STATUS "Setting Intel Compiler compatibity mode to gcc 4.5 for nvcc host compilation")
-           set(CUDA_HOST_COMPILER_OPTIONS "${CUDA_HOST_COMPILER_OPTIONS};-Xcompiler;-gcc-version=450;")
-       endif()
-   endif()
+#   if (UNIX AND CMAKE_C_COMPILER_ID MATCHES "Intel" AND
+#       CUDA_HOST_COMPILER_AUTOSET)
+#       if (CUDA_VERSION VERSION_LESS "4.1")
+#           message(STATUS "Setting Intel Compiler compatibity mode to gcc 4.4 for nvcc host compilation")
+#           set(CUDA_HOST_COMPILER_OPTIONS "${CUDA_HOST_COMPILER_OPTIONS};-Xcompiler;-gcc-version=440;")
+#       else()
+#           message(STATUS "Setting Intel Compiler compatibity mode to gcc 4.5 for nvcc host compilation")
+#           set(CUDA_HOST_COMPILER_OPTIONS "${CUDA_HOST_COMPILER_OPTIONS};-Xcompiler;-gcc-version=450;")
+#       endif()
+#   endif()
    set(CUDA_HOST_COMPILER_OPTIONS "${CUDA_HOST_COMPILER_OPTIONS}"
        CACHE STRING "Options for nvcc host compiler (do not edit!)." FORCE)
```

#### int128.patch

```

--- src/external/boost/boost/config/compiler/intel.hpp.orig 2014-06-18 00:14:19.000000000 +0900
+++ src/external/boost/boost/config/compiler/intel.hpp 2014-07-09 09:59:27.000000000 +0900
@@ -35,10 +35,14 @@
 #endif

 #ifdef BOOST_INTEL_STDCXX0X
+#ifndef BOOST_COMPILER
 #define BOOST_COMPILER "Intel C++ C++0x mode version " BOOST_STRINGIZE(BOOST_INTEL_CXX_VERSION)
+#endif
 #else
+#ifndef BOOST_COMPILER
 #define BOOST_COMPILER "Intel C++ version " BOOST_STRINGIZE(BOOST_INTEL_CXX_VERSION)
 #endif
+#endif
 #define BOOST_INTEL BOOST_INTEL_CXX_VERSION

 #if defined(_WIN32) || defined(_WIN64)
@@ -303,10 +307,6 @@
 # define BOOST_HAS_STDINT_H
 #endif

-#if defined(__LP64__) && defined(__GNUC__) && (BOOST_INTEL_CXX_VERSION >= 1310)
-# define BOOST_HAS_INT128
-#endif
-
//
// last known and checked version:
#if (BOOST_INTEL_CXX_VERSION > 1310

```

## ビルド手順

```

#!/bin/csh -f
umask 022
set file_gromacs=/home/users/${USER}/build/gromacs506/gromacs-5.0.6.tar.gz
set file_patch1=/home/users/${USER}/build/gromacs506/no-gcc-version.patch
set file_patch2=/home/users/${USER}/build/gromacs506/int128.patch
set prefix_avx256=/local/apl/pg/gromacs506
set work=/work/users/${USER}
source /opt/intel/composer_xe_2015.2.164/bin/compilervars.csh intel64
#-----
cd ${work}
if (-d gromacs-5.0.6) then
  mv gromacs-5.0.6 gromacs-erase
  rm -rf gromacs-erase &
endif
tar xzf ${file_gromacs}
cd gromacs-5.0.6
patch -p0 < ${file_patch1}
patch -p0 < ${file_patch2}
#
setenv CC icc
setenv CXX icpc
setenv F77 ifort
setenv F90 ifort
setenv FC ifort
mkdir rccs-gpu
cd rccs-gpu
cmake28 .. -DCMAKE_INSTALL_PREFIX=${prefix_avx256} \
  -DCMAKE_VERBOSE_MAKEFILE=ON \
  -DGMX_MPI=OFF \
  -DGMX_GPU=ON \
  -DGMX_DOUBLE=OFF \
  -DGMX_THREAD_MPI=OFF \
  -DGMX_FFT_LIBRARY=mpi \

```

```

-DGMX_FFT_LIBRARY=mkl \
-DGMX_SYMLINK_OLD_BINARY_NAMES=OFF \
-DREGRESSIONTEST_DOWNLOAD=OFF
make -j 12
make install
cd ..
#
mkdir rccs-d
cd rccs-d
cmake28 .. -DCMAKE_INSTALL_PREFIX=${prefix_avx256} \
  -DCMAKE_VERBOSE_MAKEFILE=ON \
  -DGMX_MPI=OFF \
  -DGMX_GPU=OFF \
  -DGMX_DOUBLE=ON \
  -DGMX_THREAD_MPI=OFF \
  -DGMX_FFT_LIBRARY=mkl \
  -DGMX_SYMLINK_OLD_BINARY_NAMES=OFF \
  -DREGRESSIONTEST_DOWNLOAD=OFF
make -j 12
make install
cd ..
#
setenv CC mpiicc
setenv CXX mpiicpc
setenv F77 mpiifort
setenv F90 mpiifort
setenv FC mpiifort
mkdir rccs-mpi
cd rccs-mpi
cmake28 .. -DCMAKE_INSTALL_PREFIX=${prefix_avx256} \
  -DCMAKE_VERBOSE_MAKEFILE=ON \
  -DGMX_MPI=ON \
  -DGMX_GPU=OFF \
  -DGMX_DOUBLE=OFF \
  -DGMX_THREAD_MPI=OFF \
  -DGMX_FFT_LIBRARY=mkl \
  -DMPIDIR=/opt/intel/impi/5.0.3.048/intel64/bin/mpirun \
  -DGMX_SYMLINK_OLD_BINARY_NAMES=OFF \
  -DREGRESSIONTEST_DOWNLOAD=OFF
make -j 12
make install
cd ..
#
mkdir rccs-mpi-d
cd rccs-mpi-d
cmake28 .. -DCMAKE_INSTALL_PREFIX=${prefix_avx256} \
  -DCMAKE_VERBOSE_MAKEFILE=ON \
  -DGMX_MPI=ON \
  -DGMX_GPU=OFF \
  -DGMX_DOUBLE=ON \
  -DGMX_THREAD_MPI=OFF \
  -DGMX_FFT_LIBRARY=mkl \
  -DMPIDIR=/opt/intel/impi/5.0.3.048/intel64/bin/mpirun \
  -DGMX_SYMLINK_OLD_BINARY_NAMES=OFF \
  -DREGRESSIONTEST_DOWNLOAD=OFF
make -j 12
make install
cd ..

```